


PRODUCT DESCRIPTION:

FIPRO® Light 500 is a non-combustible Vermiculite board with smooth surface and in large sizes. It is particularly easy and clean for processing. The surface of **FIPRO® Light 500** can be covered with many finishing materials.



FIPRO® Light 500

Technical specification *

Reaction to fire (IMO Res. MSC 307(88) FTP (2010))	Non-combustible
Density	500 kg/m ³ (+/- 10%)
Standard dimension or on request	2440 x 1220 mm 2500 x 1250 mm, 2800 x 1250 mm 3100 x 1250 mm
Tolerance in dimension	+/- 1.0 mm
Standard thickness or on request	10, 12, 16, 19, 22, 25, 30, 35, 40, 50 mm
Tolerance in thickness	+/- 0.3 mm
Bending strength (EN 12809 Var.B)	1.5 MPa
Tensile strength (EN 319)	0.2 MPa
Residual moisture (ex works) (EN 322)	2 - 7 %

*All specified technical data are average values from the production and are for information only. Mineralka reserves the right to modify product specifications at any time without notice. Safety data sheet and manual are available on request.

Packing and weight list

Thickness mm	Weight kg/m ²	Boards/ pallet
10	5.0	95
12	6.0	79
16	8.0	60
19	9.5	50
22	11.0	43
25	12,5	38
30	15.0	32
35	17,5	27
40	20.0	24
50	25.0	19

Application areas

FIPRO® Light 500 non-combustible fire protection boards are used for C class constructions: bulkheads, ceilings, linings, doors and furniture for ships and offshore platforms.

If certain characteristics are essential for certain applications, it is best to contact us.
We are constantly expanding our construction program. For more information, please visit us at www.fipro.si.



Mineralka d.o.o.
SI-1380 Cerknica

T +386.1.709 00 00
F +386.1.709 00 02

Visit us
www.fipro.si

The content of this catalogue and information about it has been provided in good faith, under the exclusion of liability and shall not form the basis for any warranty claims. The content is provided as assistance to the Mineralka product users and resellers, who are fully responsible for their actions. Stipulations in the official document only are legally binding for the user.